



Kvaser Linx J1587

EAN: 73-30130-00389-7

Kvaser Linx is a single channel, add-on cable that provides access to a J1587 bus network. It connects to your existing Kvaser High Speed CAN interface or Datalogger in series. Compatible with selection of Kvaser CAN HS devices.

Major Features

- Works with most Kvaser CAN HS interfaces (Not compatible with Memorator Professional 5xHS).
- Create software applications using the included J1587 library.
- Supports data logging with the Kvaser Memorator Professional HS/HS.
- Log both CAN and J1587 data simultaneously.
- Trigger on J1587 MID, PID, etc.
- Molded 9 pin DSUB female connector with thumbscrews.
- Molded 9pin DSUB male connector.
- Compact plastic housing.



Warranty

- 2-Year Warranty. See our General Conditions and Policies for details.

Support

- Free Technical Support on all products available by contacting support@kvaser.com.

Software

- Documentation, software and drivers can be downloaded for free at www.kvaser.com/downloads.
- Kvaser CANLIB SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, and Visual Basic.
- All Kvaser CAN interface boards share a common software API. Programs written for one interface type will run without modifications on the other interface types!
- J2534 Application Programming Interface available.
- RP1210A Application Programming Interface available.
- On-line documentation in Windows HTML-Help and Adobe Acrobat format.



TECHNICAL DATA - KVASER LINX J1587

ERROR FRAME DETECTION	No
API, LICENCED	
WIDTH (MM)	25
SOUND	No
MSGRATE TX MAX	2000
MAXIMUM BITRATE (KBPS)	9600
MSGRATE RX MAX	2000
CONNECTOR	DSUB 9
CLOCK SYNC	No
IP CLASS	IP40
SOUND	No
RUGGED	No
LENGTH (MM)	100
WIDTH (MM)	25
MAXIMUM BITRATE (KBPS)	9600
CURRENT CONSUMPTION	Typical 200mA
CONNECTOR	DSUB 9
CASING MATERIAL	Glass Fiber Reinforced PA6
SILENT MODE	No
IP CLASS	IP40
PROMOTIONAL_TEXT	J1587
CAN FD	No
CB BOARD	No
WEIGHT (G)	100.0
ON-BOARD RX BUFFER	No
CB BOARD	No
ON-BOARD TX BUFFER	No



CASING MATERIAL	PA6
HEIGHT (MM)	20
NETWORK CHANNEL(S)	
ERROR FRAME GENERATION	No
WEIGHT (G)	100.0
EMBEDDED SCRIPT	No
PC INTERFACE	Cable
STATUS	Active
CLOCK SYNC	N/A
LENGTH (MM)	100
RUGGED	No
NETWORK CHANNEL(S)	1x J1587te
STATUS	Active
CERTIFICATIONS	CE,RoHS
ON-BOARD RX BUFFER	No
ON-BOARD BUFFER	No
DATABASE DBC SUPPORT	No
ON-BOARD TX BUFFER	No
ON-BOARD BUFFER	No
CURRENT CONSUMPTION	200mA
# OF CAN CHANNELS	1
PROMOTIONAL_TEXT	Single channel, add-on cable provides access to a J1587 bus network.
CERTIFICATIONS	CE,RoHS
OPERATING TEMPERATURE RANGE (C)	-40.00 to 85.00
SILENT MODE	No
ERROR COUNTERS READING	N/A
EMBEDDED SCRIPT	No



MSGRATE TX MAX	2000
CAN FD	No
GALVANIC ISOLATION	No
PRODUCT GROUPS	Accessory
TIMESTAMP RESOLUTION (US)	100
HEIGHT (MM)	20
ERROR FRAME DETECTION	N/A
OPERATING SYSTEM	Win 7,Win Vista,Win 10,Win 8
MINIMUM BITRATE (KBPS)	12
TIMESTAMP RESOLUTION (US)	100
API, FREE	Kvaser API
MSGRATE RX MAX	2000
API, LICENCED	None
MINIMUM BITRATE (KBPS)	N/A
PC INTERFACE	Cable
OPERATING TEMPERATURE RANGE (C)	-40.00 to 85.00
PRODUCT GROUPS	Accessory
# OF CAN CHANNELS	1
OPERATING SYSTEM	Win XP,Linux,Win 7,Win Vista,Win 10,Win 8
GALVANIC ISOLATION	No
ERROR FRAME GENERATION	No
ERROR COUNTERS READING	No
API, FREE	

The information herein is subject to change without notice