



Kvaser OBD II Extension Cable 10m

EAN: 73-30130-00348-4

Kvaser's OBD II Extension Cable is a highly durable extension cable of 10 metres in length with male to female [OBD II](#) connectors. The cable is made of high quality thermoplastic rubber to ensure excellent flexibility and resilience. All pins are connected.

Major Features

- Molded [OBD II](#) (SAE J1962) male connector, Type B (24 Volt).
- Molded OBD II (SAE J1962) female connector, Type B (24 Volt).
- Made of durable thermoplastic rubber.
- Gold plated pins on OBDII connectors for extra reliable contact.
- Termination is built in with a 120 Ohm terminating resistor.
- Available in other cable lengths.
- RoHS compliant.
- This cable can save wear and tear on your CAN interface's OBD2 connector



Warranty

- 2-Year Warranty. See our General Conditions and Policies for details.

Support

- Free Technical Support on all products available by contacting support@kvaser.com.

TECHNICAL DATA - KVASER OBD II EXTENSION CABLE 10M

# OF CAN CHANNELS	1
OPERATING SYSTEM	Linux,Win Vista,Win 10,Win 8,Win 7,Win XP
GALVANIC ISOLATION	N/A
TIMESTAMP RESOLUTION (US)	N/A
PC INTERFACE	Cable
API, LICENCED	None
WIDTH (MM)	N/A
CASING MATERIAL	Durable thermoplastic rubber
CURRENT CONSUMPTION	
PC INTERFACE	Cable
CLOCK SYNC	N/A
MINIMUM BITRATE (KBPS)	N/A
SILENT MODE	No
OPERATING SYSTEM	Win 10,Win Vista,Linux,Win 8,Win 7,Win XP
EMBEDDED SCRIPT	No
CONNECTOR	N/A
OPERATING TEMPERATURE RANGE (C)	-30.00 to 85.00
ERROR FRAME DETECTION	No
CURRENT CONSUMPTION	N/A
MSGRATE RX MAX	N/A
API, LICENCED	
ON-BOARD RX BUFFER	N/A
API, FREE	
ERROR FRAME GENERATION	No
ON-BOARD TX BUFFER	N/A
RUGGED	No
MINIMUM BITRATE (KBPS)	N/A

ERROR COUNTERS READING	No
ON-BOARD TX BUFFER	No
CERTIFICATIONS	CE,RoHS
ON-BOARD BUFFER	No
CB BOARD	No
MAXIMUM BITRATE (KBPS)	N/A
HEIGHT (MM)	N/A
CB BOARD	No
API, FREE	N/A
CASING MATERIAL	
MSGRATE TX MAX	N/A
STATUS	Active
PRODUCT GROUPS	Cable
MSGRATE TX MAX	N/A
GALVANIC ISOLATION	No
NETWORK CHANNEL(S)	
SILENT MODE	N/A
CAN FD	No
WIDTH (MM)	N/A
SOUND	No
PRODUCT GROUPS	Cable
NETWORK CHANNEL(S)	
HEIGHT (MM)	N/A
IP CLASS	
CLOCK SYNC	No
WEIGHT (G)	1000.0
TIMESTAMP RESOLUTION (US)	N/A
WEIGHT (G)	1000.0

SOUND	N/A
EMBEDDED SCRIPT	No
# OF CAN CHANNELS	1
MAXIMUM BITRATE (KBPS)	N/A
ERROR FRAME DETECTION	N/A
ERROR COUNTERS READING	N/A
LENGTH (MM)	10000
RUGGED	No
ON-BOARD RX BUFFER	No
MSGRATE RX MAX	N/A
STATUS	Active
IP CLASS	N/A
OPERATING TEMPERATURE RANGE (C)	-30.00 to 85.00
CERTIFICATIONS	CE,RoHS
CONNECTOR	N/A
ON-BOARD BUFFER	N/A
DATABASE DBC SUPPORT	No
PLAY BACK LOG FILE	No
LENGTH (MM)	10000
CAN FD	No
ERROR FRAME GENERATION	N/A

The information herein is subject to change without notice