



Kvaser Leaf Professional HS OBDII

EAN: 73-30130-00404-7

NOTE: The Kvaser Leaf Professional HS OBDII (73-30130-00404-7) has been marked "End of Life". Existing customers are encouraged to migrate to the [Kvaser Leaf Pro HS v2 OBDII\(73-30130-00849-6\)](https://www.kvaser.com/products/kvaser-leaf-pro-hs-v2-obdii/).

For more information, please [contact us](#).

Kvaser Leaf Professional is a one channel, high performance, USB interface for High Speed CAN. The [OBDII](#) connector provides easy access to vehicle diagnostics from the PC. Includes Kvaser's patented MagiSync feature for synchronized time-stamping, Galvanic Isolation for protection against voltage spikes, and Auto Transmit for placing messages on the bus at set intervals.

Major Features

Kvaser
Aminogatan 25 A SE 431 53 Mölndal SWEDEN
Kvaser Europe AB
Telephone: +46 31 886344
Email: sales@kvaser.com
<https://www.kvaser.com/>



- Interfaces the CAN bus with an [OBD2 connector](#).
- Supports High Speed CAN (ISO 11898-2)
- Handles up to 20,000 messages per second, time-stamped and synchronized with a precision of 1 microsecond.
- Auto transmit buffers, to send messages on a defined interval.
- Auto response buffers, to send messages on a defined event.
- Supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers.
- Excellent error handling.
- Supports silent mode for analyzing tools.
- Low power consumption.
- Excellent EMC performance.
- Polyurethane cabling for extreme environments.
- Galvanic isolation of the CAN bus driver stage to protect the hardware.
- Labeled CAN channel for easy identification of the supported physical layer.
- Equipped with a 110 cm (44 in.) long USB cable and a 30 cm (12 in.) long CAN cable.
- Designed for USB 2.0, backward compliant with USB 1.1.
- Quick and easy Plug-and-Play installation.
- A practically unlimited number of Kvaser Leafs can be connected via standard USB hubs for simultaneous use on a single PC.

Warranty

- 2-Year Warranty. See our General Conditions and Policies for details.

Support

- Free Technical Support on all products available by contacting support@kvaser.com.

Software

- Documentation, software and drivers can be downloaded for free at www.kvaser.com/downloads.



- Kvaser CANLIB SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, and Visual Basic.
- All Kvaser CAN interface boards share a common software API. Programs written for one interface type will run without modifications on the other interface types!
- J2534 Application Programming Interface available.
- RP1210A Application Programming Interface available.
- On-line documentation in Windows HTML-Help and Adobe Acrobat format.



TECHNICAL DATA - KVASER LEAF PROFESSIONAL HS OBDII

ERROR FRAME GENERATION	Yes
EMBEDDED SCRIPT	No
ON-BOARD RX BUFFER	Yes
RUGGED	No
MSGRATE RX MAX	2000
PC INTERFACE	USB
# OF CAN CHANNELS	1
ERROR FRAME DETECTION	Yes
PC INTERFACE	USB
CONNECTOR	OBD-II /J1962
# OF CAN CHANNELS	1
IP CLASS	IP40
CAN FD	No
GALVANIC ISOLATION	Yes
MAXIMUM BITRATE (KBPS)	1000
OPERATING SYSTEM	Win XP, Linux, Win 7, Win Vista, Win 10, Win 8
CLOCK SYNC	Yes
TIMESTAMP RESOLUTION (US)	1
TIMESTAMP RESOLUTION (US)	1
API, FREE	Kvaser API, J2534, RP 1210
OPERATING SYSTEM	Win XP, Linux, Win 7, Win Vista, Win 10, Win 8
LENGTH (MM)	100
HEIGHT (MM)	20
NETWORK CHANNEL(S)	1 x CAN HS
CERTIFICATIONS	CE, RoHS
CB BOARD	No
CASING MATERIAL	Glass Fiber Reinforced PA6

Kvaser
 Aminogatan 25 A SE 431 53 Mölndal SWEDEN
 Kvaser Europe AB
 Telephone: +46 31 886344
 Email: sales@kvaser.com
<https://www.kvaser.com/>



Kvaser Leaf Professional HS OBDII

PRODUCT GROUPS	Leaf
MSGRATE RX MAX	20000
SILENT MODE	Yes
CLOCK SYNC	Yes
ERROR FRAME GENERATION	Yes
CASING MATERIAL	PA6
DATABASE DBC SUPPORT	No
MINIMUM BITRATE (KBPS)	5
CERTIFICATIONS	CE,RoHS
API, LICENCED	
CAN FD	No
ON-BOARD RX BUFFER	Yes
CURRENT CONSUMPTION	Typical 70mA
CONNECTOR	OBD-II /J1962
ERROR FRAME DETECTION	Yes
MAXIMUM BITRATE (KBPS)	1000
IP CLASS	IP40
HEIGHT (MM)	20
OPERATING TEMPERATURE RANGE (C)	-40.00 to 85.00
OPERATING TEMPERATURE RANGE (C)	-40.00 to 85.00
GALVANIC ISOLATION	Yes
ON-BOARD BUFFER	Yes
ERROR COUNTERS READING	Yes
SILENT MODE	Yes
MSGRATE TX MAX	2000
WEIGHT (G)	100.0
API, FREE	Kvaser API, J2534, RP 1210
ERROR COUNTERS READING	Yes

Kvaser
Aminogatan 25 A SE 431 53 Mölndal SWEDEN
Kvaser Europe AB
Telephone: +46 31 886344
Email: sales@kvaser.com
<https://www.kvaser.com/>



Kvaser Leaf Professional HS OBDII

STATUS	Obsolete
ON-BOARD TX BUFFER	Yes
MSGRATE TX MAX	20000
ON-BOARD BUFFER	Yes
API, LICENCED	None
LENGTH (MM)	100
CURRENT CONSUMPTION	Typical 70mA
STATUS	Obsolete
WIDTH (MM)	25
WEIGHT (G)	100.0
CB BOARD	No
WIDTH (MM)	25
MINIMUM BITRATE (KBPS)	5
SOUND	Yes
NETWORK CHANNEL(S)	1 x CAN HS
RUGGED	No
ON-BOARD TX BUFFER	Yes
SOUND	Yes
PRODUCT GROUPS	Leaf
EMBEDDED SCRIPT	No

The information herein is subject to change without notice