



Kvaser OBD II to Dsub9 Adapter Cable

EAN: 73-30130-00723-9

A Kvaser OBD II Adapter Cable connects any Kvaser CAN bus interface with a DSUB9 female connector to any vehicle with an [OBD II](#) (J1962) connector. Supports K-Line.

Major Features

- Molded [OBD II \(SAE J1962\)](#) male connector, for Type A (12 Volt) as well as Type B (24 Volt).
- Molded 9 pin DSUB female connector with thumbscrews.
- 2500 mm (approx. 8 ft) long cable made of durable thermoplastic rubber.
- Designed for Kvaser's High-Speed, Low-Speed and Single-Wire CAN interfaces.
- Perfect for Kvaser Memorator, Kvaser Leaf Professional, etc.
- Supports K-Line.

Warranty

Kvaser
Aminogatan 25 A SE 431 53 Mölndal SWEDEN
Kvaser Europe AB
Telephone: +46 31 886344
Email: sales@kvaser.com
<https://www.kvaser.com/>



Kvaser OBD II to Dsub9 Adapter Cable

- 2-Year Warranty. See our General Conditions and Policies for details.

Support

- Free Technical Support on all products available by contacting support@kvaser.com.

TECHNICAL DATA - KVASER OBD II TO DSUB9 ADAPTER CABLE

LENGTH (MM)	2500
ON-BOARD BUFFER	No
WIDTH (MM)	N/A
ON-BOARD RX BUFFER	N/A
ERROR COUNTERS READING	No
CERTIFICATIONS	CE,RoHS
GALVANIC ISOLATION	No
ERROR COUNTERS READING	N/A
ON-BOARD TX BUFFER	N/A
# OF CAN CHANNELS	1
OPERATING SYSTEM	Win XP, Linux, Win 7, Win Vista, Win 10, Win 8
IP CLASS	N/A
ON-BOARD TX BUFFER	No
ON-BOARD RX BUFFER	No
CAN FD	No
SOUND	N/A
PC INTERFACE	Cable
SILENT MODE	No
PC INTERFACE	Cable
STATUS	Active
OPERATING SYSTEM	Win XP, Linux, Win 7, Win Vista, Win 10, Win 8
NETWORK CHANNEL(S)	
TIMESTAMP RESOLUTION (US)	N/A
API, FREE	
ERROR FRAME GENERATION	No
API, FREE	N/A
NETWORK CHANNEL(S)	

RUGGED	No
EMBEDDED SCRIPT	No
OPERATING TEMPERATURE RANGE (C)	-30.00 to 85.00
CURRENT CONSUMPTION	N/A
CASING MATERIAL	Durable thermoplastic rubber
WEIGHT (G)	160.0
# OF CAN CHANNELS	1
ON-BOARD BUFFER	N/A
CURRENT CONSUMPTION	
LENGTH (MM)	2500
CERTIFICATIONS	CE,RoHS
API, LICENCED	None
MAXIMUM BITRATE (KBPS)	N/A
DATABASE DBC SUPPORT	No
ERROR FRAME DETECTION	No
CB BOARD	No
MSGRATE TX MAX	N/A
PRODUCT GROUPS	Cable
API, LICENCED	
OPERATING TEMPERATURE RANGE (C)	-30.00 to 85.00
STATUS	Active
GALVANIC ISOLATION	N/A
CONNECTOR	N/A
CASING MATERIAL	
MINIMUM BITRATE (KBPS)	N/A
MINIMUM BITRATE (KBPS)	N/A
MSGRATE RX MAX	N/A
PRODUCT GROUPS	Cable



Kvaser OBD II to Dsub9 Adapter Cable

CONNECTOR	N/A
MSGRATE RX MAX	N/A
ERROR FRAME GENERATION	N/A
WIDTH (MM)	N/A
PLAY BACK LOG FILE	No
RUGGED	No
CAN FD	No
HEIGHT (MM)	N/A
TIMESTAMP RESOLUTION (US)	N/A
CLOCK SYNC	No
CB BOARD	No
ERROR FRAME DETECTION	N/A
IP CLASS	
EMBEDDED SCRIPT	No
MAXIMUM BITRATE (KBPS)	N/A
HEIGHT (MM)	N/A
SILENT MODE	N/A
CLOCK SYNC	N/A
MSGRATE TX MAX	N/A
SOUND	No
WEIGHT (G)	160.0

The information herein is subject to change without notice